



## U-BOLT

### Standard U-Bolt with Nuts Model 1500

**SIZE:**

Range: 1/2" thru 24"

**FINISH:**

Plain

**MATERIAL:**

Carbon steel U-bolt and four finished hex nuts

**FEATURES:**

- 4 finished hex nuts
- Conforms with Fed. Spec. WW-H-171E (Type 24), & MSS SP-69 (Type 24)

### U-BOLT: Loads (LBS) • Weights (LBS) • Dimensions (IN)

| ITEM CODE<br>1500 | ITEM CODE<br>1600 | PIPE<br>SIZE | MAX<br>LOAD | WEIGHT | A<br>ROD SIZE | B       | C       | D      | E     | F       |
|-------------------|-------------------|--------------|-------------|--------|---------------|---------|---------|--------|-------|---------|
| 1500-0050P        | 1600-0050EG       | 1/2          | 580         | 0.10   | 1/4           | 15/16   | 1 3/16  | 2 3/4  | 2 1/8 | 2 5/16  |
| 1500-0075P        | 1600-0075EG       | 3/4          | 580         | 0.10   | 1/4           | 1 1/8   | 1 3/8   | 2 3/4  | 2 1/8 | 2 7/32  |
| 1500-0100P        | 1600-0100EG       | 1            | 580         | 0.11   | 1/4           | 1 3/8   | 1 5/8   | 2 3/4  | 2 1/8 | 2 3/32  |
| 1500-0125P        | 1600-0125EG       | 1 1/4        | 1460        | 0.28   | 3/8           | 1 11/16 | 2 1/16  | 2 7/8  | 2 1/8 | 2 1/31  |
| 1500-0150P        | 1600-0150EG       | 1 1/2        | 1460        | 0.30   | 3/8           | 2       | 2 3/8   | 3      | 2 1/2 | 2 1/16  |
| 1500-0200P        | 1600-0200EG       | 2            | 1460        | 0.32   | 3/8           | 2 7/16  | 2 13/16 | 3 1/4  | 2 1/2 | 2 1/16  |
| 1500-0250P        | 1600-0250EG       | 2 1/2        | 2700        | 0.71   | 1/2           | 2 15/16 | 3 7/16  | 3 3/4  | 3     | 2 5/16  |
| 1500-0300P        | 1600-0300EG       | 3            | 2700        | 0.78   | 1/2           | 3 9/16  | 4 1/8   | 4      | 3     | 2 1/4   |
| 1500-0350P        | 1600-0350EG       | 3 1/2        | 2700        | 0.85   | 1/2           | 4 1/16  | 4 9/16  | 4 1/4  | 3     | 2 1/4   |
| 1500-0400P        | 1600-0400EG       | 4            | 2700        | 0.90   | 1/2           | 4 9/16  | 5 1/16  | 4 1/2  | 3     | 2 1/4   |
| 1500-0500P        | 1600-0500EG       | 5            | 2700        | 1.00   | 1/2           | 5 5/8   | 6 1/8   | 5      | 3     | 2 7/32  |
| 1500-0600P        | 1600-0600EG       | 6            | 4320        | 1.95   | 5/8           | 6 3/4   | 7 3/8   | 6 1/8  | 3 3/4 | 2 13/16 |
| 1500-0800P        | 1600-0800EG       | 8            | 4320        | 2.30   | 5/8           | 8 3/4   | 9 3/8   | 7 1/8  | 3 3/4 | 2 13/16 |
| 1500-1000P        | 1600-1000EG       | 10           | 6460        | 4.05   | 3/4           | 10 7/8  | 11 5/8  | 8 3/8  | 4     | 3       |
| 1500-1200P        | 1600-1200EG       | 12           | 9960        | 6.45   | 7/8           | 12 7/8  | 13 3/4  | 9 5/8  | 4     | 3 1/4   |
| 1500-1400P        | 1600-1400EG       | 14           | 9960        | 7.85   | 7/8           | 14 1/8  | 15      | 10 1/4 | 4 1/4 | 3 1/4   |
| 1500-1600P        | 1600-1600EG       | 16           | 9960        | 8.70   | 7/8           | 16 1/8  | 17      | 11 1/4 | 4 1/4 | 3 1/4   |
| 1500-1800P        | 1600-1800EG       | 18           | 11800       | 12.95  | 1             | 18 1/8  | 19 1/8  | 12 5/8 | 4 3/4 | 3 5/8   |
| 1500-2000P        | 1600-2000EG       | 20           | 11800       | 14.00  | 1             | 20 1/8  | 21 1/8  | 13 3/8 | 4 3/4 | 3 5/8   |
| 1500-2400P        | 1600-2400EG       | 24           | 11800       | 16.00  | 1             | 24 1/8  | 25 1/8  | 15 5/8 | 4 3/4 | 3 5/8   |